



## **Volatility Forecasting using Hybrid GARCH Neural Network Models: The Case of the Italian Stock Market**

**Dimitrios Kartsonakis Mademlis<sup>1\*</sup>, Nikolaos Dritsakis<sup>2</sup>**

<sup>1</sup>University of Macedonia, Egnatia 156, Thessaloniki 546 36, Greece, <sup>2</sup>University of Macedonia, Egnatia 156, Thessaloniki 546 36, Greece. \*Email: [dim.karmad@uom.edu.gr](mailto:dim.karmad@uom.edu.gr)

**Received:** 30 September 2020

**Accepted:** 01 December 2020

**DOI:** <https://doi.org/10.32479/ijefi.10842>

### **ABSTRACT**

In several financial applications, it is extremely useful to predict volatility with the highest precision. Neural Networks alongside GARCH-type models have been extensively employed in the last decades for estimating volatility of financial indices. The motivation of this survey is to decide whether combining different types of models can improve the return volatility forecasts. Thus, two hybrid models are utilized and compared with an asymmetric GARCH model and a Neural Network in terms of their ability to predict the volatility of the FTSE MIB index. The conclusions reveal that the hybrid model, which is based on a Neural Network having as inputs the returns and its historical values as well as the estimates of conditional volatility obtained by an EGARCH model, provides the best predictive power. Moreover, the dominance of this hybrid model is such that it forecast encompasses the remaining models. Finally, it is demonstrated that there are significant leverage effects in the Italian stock market.

**Keywords:** Artificial Neural Network, Forecast Encompassing, GARCH Models, Realized Volatility, Stock Market, Volatility Forecast

**JEL Classifications:** C22; C45; C53; G15

### **1. INTRODUCTION**

Modelling and forecasting stock market volatility has caused great concern among researchers and financial market participants since it is one of the most essential inputs to several financial implications from asset and option pricing to risk measurement. Volatility, with respect to financial indices, can be considered as a measure of risk or it can be thought of as the degree by which a stock price fluctuates around its average value. Predicting returns and volatilities of the assets with greater accuracy is critical for investment decisions in financial markets. Market participants employ different approaches for forecasting volatility of financial variables. According to Nazarian et al. (2013), these approaches are divided into two categories, the classic one and the Neural Network. One of the classic methods is the time series modelling of financial data with time-varying variance which has received a lot of interest. Engle (1982) was the first one to introduce such types of models (ARCH) while Bollerslev (1986) generalized

these models and provided the GARCH model. Since financial data are highly volatile, these models with heteroscedastic errors have been extensively used in finance (Ahmed and Suliman, 2011; Awartani and Corradi, 2005; Curto et al., 2009; Engle and Patton, 2007; Koopman et al., 2005; Liu and Hung, 2010; Lu and Perron, 2010 and Marcucci, 2005; Dritsaki, 2017; Kartsonakis-Mademlis and Dritsakis, 2018). However, despite their success in forecasting various variables, the results in terms of the predictive accuracy of financial data are far from satisfactory due to the fact that the classic methods (structural models) depend on information obtained from historical events. Given the non-linearities and the complex relationships in the stock markets, time-series approaches may not be able to capture these characteristics. For this reason, non-linear and more flexible models such as Neural Networks can produce better results in modeling and forecasting than linear models (Georgescu and Dinucă, 2011; Ghiassi et al., 2006; Güreşen et al., 2011; Qi, 1999; Quah, 2007; Sahin et al., 2012 and Soni, 2011; Kartsonakis-Mademlis and Dritsakis, 2020a). In addition to that,

Nazarian et al. (2013) proposed that the combination of classic and Neural Networks (hybrid models) has been the reaction of the lack of consensus regarding whether the efficient market hypothesis holds true or not since this method is able to predict future trend of prices with higher accuracy compared to the classic methods (Abounoori et al., 2013; Bildirici and Ersin, 2009; Güreşen and Kayakutlu, 2008; Hajizadeh et al., 2012; Kailas, 2012; Khan and Gour, 2013; Merh et al., 2010; Pai and Lin, 2005; Sui et al., 2007; Wang et al., 2012 and Wei et al., 2011).

One of the most crucial applications of GARCH models in finance is forecasting. Given the fact that the volatility is a key input to several financial decision-making models, the performance of a model in predicting volatility is of utmost importance (Kartsonakis-Mademlis and Dritsakis, 2020b). This is the rationale behind this research to produce more accurate volatility forecasts. To this end, we combine GARCH-type models with Artificial Neural Networks in two different ways to achieve higher predictive accuracy for the volatility of the Borsa Italiana Stock Exchange index, FTSE MIB. More specifically, we first model the return series of the stock index with an ARMA model using the Box and Jenkins (1976) methodology. In the second step, the fitness of two asymmetric GARCH models, namely, EGARCH and GJR-GARCH is evaluated and compared. In the third step, we estimate an ANN model. Then, we construct the two hybrid models, namely, the ANN-GARCH model and the GARCH-ANN model. The resulting forecasts from each of the four models (asymmetric GARCH model, ANN model and the two hybrid models) are compared with each other in terms of closeness to the realized volatility. Weekly time-series data from January 7, 1998 to December 6, 2017 was used from which 940 observations (approximately 90% of the total observations) were utilized for estimations (training set) and 100 observations (approximately 10% of the total observations) for out-of-sample forecasts (test set).

The remainder of this paper is organized as follows. Section 2 displays a brief review of the literature. Section 3 provides the methodology. Section 4 presents the data and some preliminary results. The empirical findings are analyzed in Section 5 and some concluding remarks are given in section 6.

## 2. LITERATURE REVIEW

Over the last years, the Artificial Neural Network models have proven their superiority over other models in time-series forecasts. One of the earliest studies is of Kryzanowski et al. (1993) who examined the performance of a Neural Network using financial data and seven macroeconomics variables to discriminate between stocks with positive returns and those with negative. Their findings propose that the Neural Network correctly classifies 72% of the positive/negative returns, which is considered high. Donaldson and Kamstra (1997) introduced a combination of a Neural Network with a semi-nonparametric non-linear GARCH model for capturing the impact of volatility on stock returns and evaluated its ability to forecast stock return volatility in Toronto, New York, Tokyo and London. Their out-of-sample forecast results show that their ANN model surpasses those from the GARCH, EGARCH and GJR-GARCH models.

Qi and Maddala (1999) showed a predictive improvement of a linear regression model employing a Neural Network model on stock price forecast. Their results largely hold out-of-sample. Schittenkopf et al. (2000) constructed a semi-non-parametric model to estimate conditional density utilizing a Neural Network framework. Their recurrent mixture density network was based on the basic ideas of the GARCH-type models but it was also able for modelling any continuous conditional density allowing for higher-order time-depending moments. The authors used their model on the returns of the FTSE100 and their findings support that the out-of-sample forecast slightly outperforms those of GARCH models.

Roh (2007) proposed hybrid models with time-series and Neural Network models for a stock price index volatility forecast in two ways: direction and deviation. He used the model in the stock market of South Korea and the results revealed the utility of the Neural Network forecasting combined with time-series models. Bildirici and Ersin (2009) utilized GARCH-type models and enhanced them with Neural Networks to examine the volatility of daily returns in the Istanbul stock market. Their hybrid models show improved forecasts.

Hajizadeh et al. (2012) attempted to increase the ability of GARCH-type models in forecasting the return volatility. They proposed two hybrid models based on Neural Networks and EGARCH model. Their results demonstrate that the second hybrid model produces better volatility forecasts in terms of closeness to the realized volatility. Kristjanpoller et al. (2014) tested a hybrid Neural Networks-GARCH model to forecast the volatility of three Latin-America stock markets, namely, Brazil, Chile and Mexico. Their findings support that the ANN models are able to increase the forecasting performance of the GARCH-type models and that the results are robust for various ANN specifications and volatility measures.

Lu et al. (2016) compared the volatility forecasting accuracy between two types of hybrid models combining ANN with asymmetric GARCH models, namely, EGARCH and GJR-GARCH. Their results propose that the EGARCH-ANN hybrid model outperformed the rest of the models in terms of forecasting the volatility of the Chinese energy market. Kristjanpoller and Minutolo (2016) used an ANN-GARCH model and incorporated financial variables, such as exchange rates and stock market indices, to achieve better forecasts of oil price volatility. Their findings show that the hybrid model improves the volatility forecasting accuracy by 30% as measured by HMSE.

Lahmiri (2017) compared the predictive ability of two GARCH models (GARCH and EGARCH), two hybrid models (GARCH-ANN and EGARCH-ANN) and a Neural Network with inputs a set of technical indicators. The results showed that in terms of MAE, MSE and Theil's inequality coefficient, the simple approach of a Neural Network predicted the volatility of the two exchange rates (U.S./Canada and U.S./Euro) more accurately compared to the rest of the models. Bhattacharya and Ahmed (2018) analysed the volatility of crude oil in India and their results were in favor of hybrid models over GARCH models. More specifically, they attempted to forecast the oil's volatility by comparing various

GARCH-type models with hybrid GARCH-ANN models. Based on the MSE index, they revealed that the EGARCH-ANN provided the best predictive ability among the models. However, the addition of an exchange rate (Indian Rupee/Saudi Arabia Riyal) as input in the hybrid model did not provide any further improvement. Ramos-Perez et al. (2019) utilized data from 2000 to 2017 for S&P500 and constructed a hybrid model to predict its volatility. Their hybrid model was based on machine learning techniques and they compared it with two GARCH-type-ANN models, Heston’s (1993) model and a Neural Network. The findings, based on the RMSE index, supported the superiority of their model in all five sub-periods that the sample was divided.

### 3. METHODOLOGY

#### 3.1. ARMA/GARCH-type Models

Developing and establishing ARMA models as tools for forecasting financial variables are known as the Box and Jenkins (1976) methodology. This approach in time-series analysis is a method of finding an ARMA(p,q) model that adequately describes the stochastic process from which it came the sample. The ARMA model can be expressed as follows:

$$\Phi(B)r_t - \mu = \theta(L)\varepsilon_t, \dots, \varepsilon_t | \Omega_{t-1} \sim N(0, \sigma_t^2) \tag{1}$$

where

$$\Phi(B) = 1 - \varphi_1 B - \varphi_2 B^2 - \dots - \varphi_p B^p \tag{2}$$

$$\theta(B) = 1 - \theta_1 B - \theta_2 B^2 - \dots - \theta_q B^q \tag{3}$$

where  $r_t$  is the return of the stock market index,  $N$  represents the conditional normal density with zero mean and conditional variance  $\sigma_t^2$ . Moreover,  $\Omega_{t-1}$  is the available information up to time  $t-1$ ,  $B$  is the backshift operator on  $t$  and  $\mu$  is the series mean. The polynomials  $\Phi(B)$  and  $\theta(B)$  are referring as the autoregressive (AR) and moving average (MA) terms, respectively and are assumed to have all inverted roots inside the unit circle.

In financial markets, volatility as a measure of risk has become a crucial component in various applications such as portfolio and risk management, derivative pricing, Black-Scholes model for option pricing, etc.

Several models based on the stochastic volatility process and time-series modelling have been developed as alternatives to the historical and implied volatility. Since the development of the ARCH model of Engle (1982) and the GARCH model of Bollerslev (1986), many extensions have been proposed. The most widely used models are the asymmetric EGARCH model of Nelson (1991) and the asymmetric GJR-GARCH model of Glosten et al. (1993).

##### 3.1.1. EGARCH

The Exponential Generalized Autoregressive Conditional Heteroscedasticity (EGARCH) model was proposed by Nelson (1991) to take into account the leverage effects of price fluctuation on conditional variance. This means that a negative shock (bad news) can have a greater impact on volatility than a positive shock

(good news) of the same magnitude. In the EGARCH(1,1) model the conditional variance is expressed in logarithmic form as follows:

$$\ln(\sigma_t^2) = \omega + \alpha_1 \frac{|\varepsilon_{t-1}|}{\sigma_{t-1}} + \gamma_1 \frac{\varepsilon_{t-1}}{\sigma_{t-1}} + \beta_1 \ln(\sigma_{t-1}^2) \tag{4}$$

where  $\omega$ ,  $\alpha_1$ ,  $\beta_1$  and  $\gamma_1$  are parameters for evaluation. When  $\varepsilon_{t-1}$  is positive or when there is good news, then the overall effect  $\varepsilon_{t-1}$  will be  $(\alpha_1 + \gamma_1) \varepsilon_{t-1}$ . Conversely, if  $\varepsilon_{t-1}$  is negative or there is bad news, then the overall effect  $\varepsilon_{t-1}$  will be  $(\alpha_1 - \gamma_1) \varepsilon_{t-1}$ . In other words, we consider that the term  $\varepsilon_{t-1}$  is the one that takes into account the asymmetry in the EGARCH model when the parameter  $\gamma_1 \neq 0$ . Therefore, the coefficient is the one that determines the leverage effects. In addition, when  $\gamma_1 < 0$ , then a positive shock causes less volatility compared to a negative shock of the same size (asymmetry). Finally, in the case of the EGARCH model, there are no restrictions on the parameters for evaluation, so as to avoid a negative conditional variance. In this model the conditional variance  $\sigma_t^2$  depends on both the size and the sign of  $\varepsilon_{t-1}$ .

##### 3.1.2. GJR-GARCH

Another asymmetric model to address the asymmetry of the volatility of the time-series is the GJR-GARCH (1,1) model proposed by Glosten et al. (1993). Its form is given by the following equation:

$$\sigma_t^2 = \omega + \alpha_1 \varepsilon_{t-1}^2 + \beta_1 \sigma_{t-1}^2 + \gamma_1 I_{t-1} \varepsilon_{t-1}^2 \tag{5}$$

The model is well defined if the following conditions are met:

$$\alpha_1 + \beta_1 + \frac{1}{2} \gamma_1 < 1 \tag{6}$$

$$\omega \geq 0, \alpha_1 \geq 0, \beta_1 \geq 0 \text{ and } \alpha_1 + \gamma_1 \geq 0 \tag{7}$$

where  $\omega$ ,  $\alpha_1$ ,  $\beta_1$  and  $\gamma_1$  are parameters for evaluation.  $I_{t-1}$  is a dummy variable which takes the value 1 if  $\varepsilon_{t-1} < 0$  and 0 otherwise. The above model Eq. 5 suggests that the bad news ( $\varepsilon_t < 0$ ) and the good news ( $\varepsilon_t > 0$ ) may have different impacts on the conditional variance. If the coefficient  $\gamma_1$  is positive, then there is asymmetry and so leverage effects. The leverage effect is described by the sum  $(\alpha_1 + \gamma_1)$  in negative shocks, which is greater than the push  $(\alpha_1)$  in positive shocks.

The parameters of the GARCH models were estimated employing the maximum likelihood method. In the case of Student-t distribution for the independent and identically distributed random variable  $z_t$  ( $z_t = \varepsilon_t / \sigma_t$ ) the following log likelihood function needs to be maximized:

$$L(\theta) = T \left[ \ln \Gamma \left( \frac{\nu+1}{2} \right) - \ln \Gamma \left( \frac{\nu}{2} \right) - \frac{1}{2} \ln (\pi (\nu-2)) \right] - \frac{1}{2} \sum_{t=1}^T \left[ \ln (\sigma_t^2) + (1+\nu) \ln \left( 1 + \frac{z_t^2}{\nu-2} \right) \right] \tag{8}$$

where  $\Gamma(\nu) = \int_0^\infty e^{-x} x^{(\nu-1)} dx$  is the gamma function and  $\nu$  denotes the degrees of freedom. Considering the standard Generalized

Error Distribution (GED), the log likelihood function takes the following form:

$$L(\theta) = \sum_{t=1}^T \left[ \ln\left(\frac{v}{\delta}\right) - \frac{1}{2} \left| \frac{z_t}{\delta} \right|^v - (1+v^{-1}) \ln(2) \right] - \ln \Gamma\left(\frac{1}{v}\right) - \frac{1}{2} \ln(\sigma_t^2) \quad (9)$$

$$\text{where } \delta = \left[ \frac{1}{2^{2/v}} \frac{\Gamma\left(\frac{1}{v}\right)}{\Gamma\left(\frac{3}{v}\right)} \right]^{1/2} \quad (\text{Dritsaki, 2017}).$$

In order to select between these two asymmetric GARCH-type models, the maximum log-likelihood value, the Akaike information criterion (AIC), the Schwarz information criterion (SIC) and the Hannan-Quinn information criterion were utilized.

### 3.2. Artificial Neural Network (ANN) Model

As we mentioned before, in stock markets there are non-linearities that cannot be captured by GARCH models which assume a linear correlation structure among the data (Fahimifard et al., 2009). Therefore, by employing linear models to deal with such complex problems may not produce adequate results. An ANN is a computational model that attempts to mimic the ability of human brain to process data and extract patterns (Luo and Shah, 2007). Based on the construction of human brain, a set of neurons is connected and organized in layers. These layers are consisting of input layers, hidden layers and output layers.

One of the greatest merits of such models is that, at least theoretically, they are able of approximating any continuous function, meaning that the researchers do not need to assume any hypotheses about the underlying model (Pakdaman et al., 2017).

Neural networks are separated into two categories, feed-forward and feedback networks. Both networks consist of neurons that are connected to each other, permitting a neuron to impact other neurons. Feed-forward networks allow signals to travel only from input to output while feedback networks allow a two-way communication by introducing loops in the network. Moreover, feed-forward Neural Networks with the back propagation algorithm permits the model to re-evaluate its parameters, through a stochastic gradient descent, so that they are in alignment with the loss function during the estimation process (Lu et al., 2016). Stochastic gradient descent is an optimization algorithm which minimizes the quadratic error. In other words, this survey utilizes the back propagation Neural Network (the so-called BPNN), which is the most widely used in financial applications (see among others, Hajizadeh et al., 2012; Ko, 2009; Lu et al., 2016; Tseng et al., 2008 and Wang, 2009).

To deal with the possibility of overfitting the training set and failing to capture the true statistical process of the data, we set only one hidden layer. In general, by increasing the number of hidden layers, the danger of overfitting is also raising which results to poor out of sample forecasting performance.

We chose one input layer, one hidden layer and one output layer. All three layers can be represented as vectors. The input layer  $d = (x_1, x_2, \dots, x_d)'$ , the hidden layer  $m = (h_1, h_2, h_3)'$  and the output layer  $c = (y_1)'$ . The back propagation Neural Network is derived by a weighted linear summation of the inputs in the following way:

$$a_j = \sum_{i=1}^d w_{ji} x_i \quad (10)$$

In order to activate the hidden unit  $j$  we transform the linear summation of Eq. 10 by employing a logistic activation function  $g(a)$ :

$$h_j = g\left(\sum_{i=1}^d w_{ji} x_i\right) \quad (11)$$

where

$$g(a) = \frac{\exp(a)}{(1 + \exp(a))} \quad (12)$$

The neuron of the output layer is given by:

$$y_1 = g\left(\sum_{j=1}^3 w_{1j} g\left(\sum_{i=1}^d w_{ji} x_i\right)\right) \quad (13)$$

where corresponds to the number of the inputs ( $i=1,2,\dots,d$ ),  $j$ , corresponds to the number of hidden neurons which are three ( $j = 1,2,3$ ),  $w_{ji}$  are the weights from the input layer to the hidden layer and  $w_{1j}$  are the weights from the hidden layer towards the output layer.

Moreover, to extract valuable results, it is important to normalize the data prior to feeding them into the Neural Network. To this end, we apply the min-max feature scaling which brings all the values of the data into the range  $[0,1]$  and is given by the following formula:

$$x' = \frac{x - x_{\min}}{x_{\max} - x_{\min}} \quad (14)$$

where  $x$  is the original data,  $x_{\min}$  and  $x_{\max}$  are the minimum and the maximum of the data, respectively and  $x'$  is the normalized data. The output of the Neural Network is then de-normalized by using the Eq. 14 solved for  $x$ .


Figure 1 displays the architecture of the three-layer back propagation Neural Network that will be used in this survey. Furthermore, the dataset is divided into two subsets in order to construct an adequate Neural Network with real financial data, the training set which consists of 90% of the total observations and the test set with the remaining 10% (Lewis, 2017. p. 53).

### 3.3. Hybrid Model

In this research, we implement two hybrid models following, in some way, the work of Lu et al. (2016) for forecasting volatility of the stock market index. Initially, an ARMA model is constructed by employing the Box-Jenkins methodology and the preferred GARCH-type model (either EGARCH or GJR-GARCH model) is identified based on some criteria (Maximum Likelihood, Akaike, Schwarz and Hannan-Quinn) upon which the hybrid models are built. Then, a Neural Network is estimated from selected explanatory input variables.



**Figure 1:** Three-layer feed-forward back propagation Neural Network



Source: Compiled by authors

**3.3.1. Type I Hybrid Model: ANN-ARMA-GARCH**

Type I model is constructed by inputting the conditional volatility outcome of the ARMA-GARCH-type model into ANN. In other words, the output of the preferred ARMA-GARCH model, i.e. the estimated conditional variance, is considered as an input variable to the ANN model in order to enhance its forecasting performance regarding the volatility of the stock market index.

**3.3.2. Type II Hybrid model: ARMA-GARCH-ANN**

Type II model is constructed by incorporating the output layer of the ANN model, i.e.  $y_1$ , as a variable to the variance equation of the ARMA-GARCH-type model.

EGARCH-ANN

$$\ln(\sigma_t^2) = \omega + \alpha_1 \frac{|\varepsilon_{t-1}|}{\sigma_{t-1}} + \gamma_1 \frac{\varepsilon_{t-1}}{\sigma_{t-1}} + \beta_1 \ln(\sigma_{t-1}^2) + \xi_1 y_1 \quad (15)$$

GJR-GARCH-ANN

$$\sigma_t^2 = \omega + \alpha_1 \varepsilon_{t-1}^2 + \beta_1 \sigma_{t-1}^2 + \gamma_1 I_{t-1} \varepsilon_{t-1}^2 + \xi_1 y_1 \quad (16)$$

Figure 2 gives a visual representation of the process of constructing the four competitive models.

**3.4. Forecast Encompassing**

In order to examine the relative properties of the forecast series, two forecast encompassing tests are conducted following the work of Cook (2012). The first one is the Fair and Shiller (1989) test. This test can be derived from the following regression:

$$RV_t = c + \lambda_1 f_{1,t} + \lambda_2 f_{2,t} + u_t \quad (17)$$

where  $RV_t$  is the realized volatility,  $c$  is a constant,  $f_{1,t}$  is the forecast of the volatility made from model 1 and  $f_{2,t}$  is the forecast of the volatility made from model 2. When  $\lambda_1 = 0$  and  $\lambda_2 \neq 0$ , the model

2 forecast encompasses (outperforms) the model 1. Contrariwise, the model 1 forecast encompasses model 2 if  $\lambda_1 \neq 0$  and  $\lambda_2 = 0$ . In the case that both  $\lambda_1 \neq 0$  and  $\lambda_2 \neq 0$  then we fail to reject the null hypothesis and both forecasts contain independent information.

The second test is based on the ability of one forecast in explaining the error of another. Forecast error can be considered as the information that a forecast failed to capture. Denoting the forecast error as  $e_{i,t} = RV_t - f_{i,t}$ , the regressions of the Chong and Hendry (1986) test are given as follows:

$$e_{1,t} = \lambda_2 f_{2,t} + v_{1,t} \quad (18)$$

$$e_{2,t} = \lambda_1 f_{1,t} + v_{2,t} \quad (19)$$


If the forecast error of model 1 ( $e_{1,t}$ ) is not related to the forecast of model 2 ( $f_{2,t}$ ), i.e.  $\lambda_2 = 0$ , then forecast 1 can be used individually. On the contrary, if the forecast error is impacted by the other forecast, then a composite forecast should be formatted including both  $f_{1,t}$  and  $f_{2,t}$ .

**4. DATA CHARACTERISTICS**

The weekly prices from January 7, 1998 to January 6, 2016 are considered as the training samples (940 observations), while those from January 13, 2016 to December 6, 2017 are used as the testing samples (100 observations). The dataset is comprised of weekly prices of the Italian stock market index, namely, FTSE MIB<sup>1</sup> (hereafter, MIB). This study utilizes weekly data because it is less noisy. We use weekly data on the Wednesday closing prices due to the fact that in general there are fewer holidays on Wednesdays than Fridays. Any missing data on Wednesday

1 Index code in Yahoo Finance database is FTSEMIB.MI. The index is measured in national units.

Figure 2: Flowchart of the modelling process



Source: Compiled by authors

closes was replaced with the closing prices from the most recent successful trading session. Stock data was obtained from Yahoo Finance. In agreement with previous studies, the continuously compounded weekly returns  $r_t$  were computed as the first log-difference,  $r_t = 100 \times \ln(P_t/P_{t-1})$ , where  $P_t$  is the weekly closing price. Table 1 presents the preliminary statistical characteristics of the return series of the training set.

The series presents a negative mean and its standard deviation is larger than the mean value. The series displays negative skewness and a large amount of kurtosis, a fairly common occurrence in high-frequency financial data which implies that GARCH-type models are adequate. In addition, the null hypothesis of normality is rejected by the Jarque and Bera (1980) test statistic at 1% level of significance. The (squared) Q-statistic of Ljung and Box (1978) which is used for detection of (heteroscedasticity) autocorrelation is significant, implying that the past behavior of the market may be more relevant. Finally, the Augmented Dickey and Fuller (1979; 1981) unit root test indicates that the return series is stationary at the 1% level of significance.

Figures 3 and 4 display the weekly prices and the returns of the MIB index for the experimental dataset, respectively.

Table 1: Preliminary statistics of weekly returns of MIB

Mean	-0.0256	Q(2)	2.9281
Stn. Dev.	3.3447	Q(4)	15.0292***
Median	0.1999	Q(6)	16.2340**
Min	-14.7353	Q <sup>2</sup> (2)	81.4003***
Max	11.6608	Q <sup>2</sup> (4)	116.2254***
Skewness	-0.3862	Q <sup>2</sup> (6)	144.1580***
Kurtosis	4.8032	ADF	-32.1799***
Jarque-Bera	152.0795***	Obs.	939

\*\*\* and \*\*Indicate statistical significance at 1% and 5%, respectively. ADF denotes the Augmented Dickey-Fuller tests (Dickey and Fuller, 1979). The lag lengths for ADF equations were selected using the Schwarz Information Criterion (SIC). MacKinnon (1996) critical values for rejection of the hypothesis of unit root applied. Q(i) and Q<sup>2</sup>(i) are the Ljung-Box statistics for serial correlation of the series and squared series at  $i^{\text{th}}$  lags (Ljung and Box, 1978)

To evaluate forecast accuracy, this survey is in agreement with the work of Pagan and Schwert (1990) (Day and Lewis, 1992; Franses and Van Dijk, 1996; and Wei, 2002) and compares the volatility forecasts of the four models with realized volatility. The realized volatility<sup>2</sup> (RV) on day  $t$  is computed as follows:

2 As a robustness check, we found that our overall conclusions in this paper hold even if we use different RV proxies, i.e. the squared returns  $RV_t = r_t^2$  (see, Brooks, 1998 and Patton, 2011).

Figure 3: MIB index price





Figure 4: MIB index returns



$$RV_t = (r_t - \bar{r})^2 \tag{20}$$

where  $\bar{r}$  is the average logarithmic return. Moreover, three metrics are utilized to evaluate the performance of the models in forecasting volatility, namely, mean absolute error (MAE), symmetric mean absolute percentage error (SMAPE) and root square error (RMSE). The metrics are defined as:

$$MAE = \frac{1}{n} \sum_{i=1}^n |\sigma_i - RV_i| \tag{21}$$

$$SMAPE = \frac{1}{n} \sum_{i=1}^n \frac{|\sigma_i - RV_i|}{|\sigma_i| + |RV_i|} \tag{22}$$

$$RMSE = \sqrt{\frac{1}{n} \sum_{i=1}^n (\sigma_i - RV_i)^2} \tag{23}$$

### 5. EMPIRICAL RESULTS

This study focuses only on the orders  $p = 1$  and  $q = 1$  of the GARCH-type models, namely, EGARCH(1,1) and GJR-GARCH(1,1). As Brooks (2008) stated, GARCH(1,1) will be sufficient to capture the volatility clustering in financial data and rarely any higher-order model is estimated. Since the kurtosis of returns exceeds the value 3, which indicates the necessity of fat-tailed distribution to describe the return series, student  $t$  and GED distributed errors were considered.

According to the Box-Jenkins methodology, ARMA(2,2) model is the preferred one to model the mean features of the return series. Table 2 presents the coefficients of the ARMA model as well as

its residual diagnostics. The findings propose that the returns of the MIB index are negatively influenced by its lagged returns at time  $t-1$  (-1.200) and  $t-2$  (-0.979). Moreover, Q statistics indicate that this specification is adequate enough to capture the serial correlation, however, considering the squared Q statistics and the ARCH tests, the null hypothesis of the absence of conditional heteroscedasticity is highly rejected. Therefore, the need of GARCH models to fit the conditional heteroscedasticity of the underlying residuals is confirmed.

Table 3 shows the values of the information criteria for each of the two competitive asymmetric GARCH models, namely EGARCH(1,1) and GJR-GARCH(1,1), as well as for each distribution under consideration. It is apparent that the EGARCH(1,1) model with GED distributed errors is the best-fitted model since Akaike, Schwarz and Hannan-Quinn criteria take their lowest values while Log-Likelihood takes its maximum value. Thus, it is the selected model for the construction of the hybrid models.

The estimated results from the ARMA(1,1)-EGARCH(1,1) with GED errors are presented in Table 4. Since the parameter is  $\gamma$  statistically significant and negative there are leverage effects in the Italian stock market. This indicates that the fluctuation of the stock price in the Italian market has an asymmetric influence on the volatility of the MIB index. This finding proposes that the investors in the Italian stock market are likely to make irrational decisions. Furthermore, based on the residual diagnostics, the model performs well, having captured the remaining ARCH effects.

Before moving to the construction of the hybrid models, we performed the forecast encompassing test of Chong and Hendry (1986) utilizing the forecasts obtained from the ARIMA(1,1)-EGARCH(1,1) model and the ANN and the results are shown in Table 5. From the first regression, we can see that the residuals obtained from the EGARCH model ( $e_{EGARCH} = RV - f_{EGARCH}$ ) are affected by the forecasts of the ANN. The same holds true from the opposite direction as the second regression suggests. This implies that both forecasts series should be included in the formation of a composite forecast series. For this reason, we use a simple mean forecast (from now on, SM) based on the forecasts of EGARCH model and ANN. In other words, we implement a weighted mean with equal weights, i.e. for both EGARCH forecasts and ANN forecasts the weights equal to 0.5. The SM forecasts will also be compared with the rest of the out-of-sample forecasts.

For establishing the Neural Network and the two hybrid models we utilized the following specifications. We used three neurons in the hidden layer and one neuron in the output layer. The target variable is the realized volatility. Moreover, the back propagation algorithm was employed with learning rate and threshold set to 0.01. We also utilized the sum of squared errors as the loss function, the min-max feature scaling formula for the normalization of the data and for all layers we used the same activation function, namely the logistic function. Regarding the selection of the inputs, this paper is in line with the work of Maciel and Ballini (2010) that used lagged values of their variables as inputs to the Neural Network by applying autocorrelation analysis.

**Table 2: Parameters estimation of ARMA model using the training set**

Parameter	c	AR(1)	AR(2)	MA(1)	MA(2)
Coefficient	-0.025	-1.200***	-0.979***	1.175***	0.952***
Residual diagnostics					
Q(8)	6.637	Q <sup>2</sup> (8)	139.54***	ARCH(6)	15.116***
Q(12)	7.971	Q <sup>2</sup> (12)	164.98***	ARCH(8)	11.702***
Q(16)	13.615	Q <sup>2</sup> (16)	194.82***	ARCH(12)	8.633***
Q(18)	14.442	Q <sup>2</sup> (18)	205.02***		
Q(22)	20.973	Q <sup>2</sup> (22)	214.72***		
Q(24)	21.996	Q <sup>2</sup> (24)	222.68***		

\*\*\*Indicates statistical significance at 1%. Q(i) and Q<sup>2</sup>(i) are the Ljung-Box statistics for serial correlation of the series and squared series at i<sup>th</sup> lags (Ljung and Box, 1978). ARCH(i) represents the F-statistic of ARCH test of Engle (1982) at i<sup>th</sup> lags.

**Table 3: Values of information criteria**

Model	Distribution	Log-Likelihood	Akaike	Schwarz	Hannan-Quinn
EGARCH	t-Student	-2348.843	5.024	5.076	5.044
	GED	<b>-2348.352</b>	<b>5.023</b>	<b>5.075</b>	<b>5.043</b>
GJR-GARCH	t-Student	-2351.675	5.030	5.082	5.050
	GED	-2353.584	5.034	5.086	5.054

Numbers in bold indicate the optimal values

**Table 4: Parameters estimation of EGARCH model using the training set**

Parameter	ω	α	γ	β
Coefficient	-0.099***	0.228***	-0.083***	0.963***
Residual diagnostics				
Q(8)	8.652*	Q <sup>2</sup> (8)	4.925	ARCH(6) 0.755
Q(12)	9.501	Q <sup>2</sup> (12)	5.770	ARCH(8) 0.634
Q(16)	12.469	Q <sup>2</sup> (16)	7.264	ARCH(12) 0.467
Q(18)	14.183	Q <sup>2</sup> (18)	7.264	
Q(22)	24.198	Q <sup>2</sup> (22)	7.602	
Q(24)	27.084	Q <sup>2</sup> (24)	9.858	

\*\*\* and \*Indicate statistical significance at 1% and 10%, respectively. Q(i) and Q<sup>2</sup>(i) are the Ljung-Box statistics for serial correlation of the series and squared series at i<sup>th</sup> lags (Ljung and Box, 1978). ARCH(i) represents the F-statistic of ARCH test of Engle (1982) at i<sup>th</sup> lags.

**Table 5: Forecast encompassing (EGARCH/ANN) for the whole test set**

Regression	Dep. var.	f <sub>EGARCH</sub>	f <sub>ANN</sub>
1			0.621***
2	e <sub>EGARCH</sub> e <sub>ANN</sub>	0.154*	

Dep. Var. indicates the dependant variables. \*\*\* and \* indicates statistical significance at 1% and 10%, respectively

In the same way, we decide to feed the Neural Network with the returns of the MIB index and its lagged values at time t-1 and t-2 following the results of the Box-Jenkins methodology (see also, the mean equation of the ARMA model in Table 2 consists of two autoregressive terms, AR(1) and AR(2). Furthermore, for the construction of the Hybrid model Type I (ANN-ARMA-GARCH), apart from the returns and its lagged values, the estimated conditional volatility ( $\hat{\sigma}_t^2$ ) from the EGARCH model was also considered as input.

In order to extract more reliable results, we compare the predictive ability of the four competitive models in both in-sample and out-of-sample forecasts while testing four different time horizons, namely, 4-, 25-, 50- and 100-weeks ahead. The two following Tables 6 and 7 show the values of the metrics for each model based on the de-normalized forecasts. Figures 5 and 6 present the plots

**Table 6: Volatility in-sample forecasting performance**

Metric	EGARCH	ANN	Hybrid I	Hybrid II
4-weeks ahead				
MAE	9.948	5.758	<b>3.536</b>	8.085
SMAPE	0.736	0.598	<b>0.499</b>	0.705
RMSE	10.428	5.838	<b>3.756</b>	9.441
25-weeks ahead				
MAE	10.667	5.019	<b>2.857</b>	7.649
SMAPE	0.642	0.511	<b>0.423</b>	0.578
RMSE	12.454	5.418	<b>3.151</b>	10.030
50-weeks ahead				
MAE	10.122	6.484	<b>2.608</b>	7.778
SMAPE	0.563	0.471	<b>0.343</b>	0.502
RMSE	13.636	11.385	<b>2.960</b>	12.375
100-weeks ahead				
MAE	9.898	7.162	<b>2.830</b>	8.335
SMAPE	0.591	0.527	<b>0.399</b>	0.556
RMSE	13.905	11.808	<b>3.159</b>	13.034

Numbers in bold indicate the optimal values

**Table 7: Volatility out-of-sample forecasting performance**

Metric	EGARCH	ANN	Hybrid I	Hybrid II	SM
4-weeks ahead					
MAE	42.550	9.045	<b>3.720</b>	84.527	22.234
SMAPE	0.517	0.321	<b>0.128</b>	0.518	0.326
RMSE	62.752	10.769	<b>3.982</b>	99.215	29.289
25-weeks ahead					
MAE	22.872	9.088	<b>3.422</b>	26.777	14.689
SMAPE	0.553	0.439	<b>0.282</b>	0.505	0.455
RMSE	33.216	15.933	<b>3.810</b>	45.491	19.996
50-weeks ahead					
MAE	17.212	8.331	<b>3.001</b>	18.213	12.010
SMAPE	0.551	0.454	<b>0.303</b>	0.514	0.482
RMSE	25.570	14.518	<b>3.404</b>	33.634	16.793
100-weeks ahead					
MAE	10.686	7.059	<b>2.957</b>	11.175	8.435
SMAPE	0.604	0.576	<b>0.455</b>	0.585	0.580
RMSE	18.477	11.228	<b>3.245</b>	24.070	12.526

Numbers in bold indicate the optimal values. SM denotes the simple mean forecast of the EGARCH and ANN models

of the predicted volatilities against the realized volatility for the in-sample and out-of-sample forecasts, respectively.




**Table 8: Forecast encompassing (Fair and Shiller) for the out-of-sample 100-weeks horizon**


Regression	Constant	$f_{Hybrid\ I}$	$f_{EGARCH}$	$f_{ANN}$	$f_{(Hybrid\ II)}$	$f_{SM}$
1	-2.674***	1.016***	0.129***			
2	-1.407***	1.056***		-0.033		
3	-1.478***	1.005***			0.019	
4	-2.010***	0.993***				0.088

The dependent variable in each of the four regressions is the realized volatility ( $RV_t$ ). \*\*\* indicates statistical significance at 1%

**Figure 5: In-sample volatility forecasts**



**Figure 6: Out-of-sample volatility forecasts**



The results of the in-sample volatility forecasts are reported in Table 6. It is clear that the Hybrid Type I model (ANN-ARMA(1,1)-GARCH(1,1)-GED) outperforms the remaining models with respect to their predictive ability in all time horizons and for all de-normalized metrics. The second-best model for predicting the volatility of the MIB index is the simple Neural Network while the volatility forecasting precision of the two GARCH-based models is far from satisfactory, with the EGARCH model being the worst. It is also interesting the fact that the metrics are getting better (smaller in values) as the time horizon of prediction is increasing, with the most accurate forecasts obtained in the 50-weeks horizon.

Turning our interest to the out-of-sample volatility forecasts, Table 7 uncovers the same pattern, which is the superiority of the Hybrid Type I model against the rest of the models in terms of closeness to the realized volatility for all cases. The ANN model again comes second while in this case, the Hybrid II model predicts the volatility of the MIB index in the poorest way. Moreover, the longer the time horizon is, the better the models perform, as indicated by the lower values of the MAE and the RMSE metrics.

**Table 9: Forecast encompassing (Chong and Hendry) for the out-of-sample 100-weeks horizon**

Regression	Dep. var.	$f_{Hybrid\ I}$	$f_{EGARCH}$	$f_{ANN}$	$f_{Hybrid\ II}$	$f_{SM}$
1	$e_{Hybrid\ I}$		-0.019			
2	$e_{EGARCH}$	0.659***				
3	$e_{Hybrid\ I}$			-0.018		
4	$e_{ANN}$	0.193***				
5	$e_{Hybrid\ I}$				0.006	
6	$e_{Hybrid\ II}$	-0.340***				
7	$e_{Hybrid\ I}$					-0.025
8	$e_{SM}$	0.426***				

Dep. Var. indicates the dependant variables. \*\*\* indicates statistical significance at 1%

However, this is not the case considering the SMAPE metric. The SM forecasts perform slightly worse than the ANN forecasts, yet better than those from the EGARCH model. However, this composite forecast is not able to reach the predictive power of the Hybrid I model. As we expected, the values of the metrics in the out-of-sample forecasts are greater than the corresponding ones in the in-sample forecasts highlighting that fitted data is generally closer to the real data than the forecasted ones.

Next, to further test the results obtained from the forecasting performance based on the three metrics, i.e. the superiority of the Hybrid I model, we conduct two forecasting encompassing tests. The first one is the Fair and Shiller (1989) test and the results are shown in Table 8. All regressions have as dependent variable the realized volatility ( $RV_t$ ). From the first regression, we ascertain that both forecasts' ( $f_{Hybrid\ I}$ ) and ( $f_{EGARCH}$ ) coefficients are significantly different from zero meaning that neither of these models encompasses the other. In other words, both models contain independent information for 100-weeks ahead forecasting of  $RV_t$ . However, from the remaining regressions, it is clear that only the individual coefficients of the  $f_{Hybrid\ I}$  are statistically significant indicating that the Hybrid's I forecasts encompass those of ANN, Hybrid II and SM.

Table 9 presents the results of the second forecast encompassing test used in this research, i.e. the Chong and Hendry (1986) test. Regarding the first regression of this Table and as indicated by the insignificant coefficient, the  $f_{EGARCH}$  fails to capture information that the Hybrid I model has missed. The same applies to the  $f_{ANN}$ ,  $f_{Hybrid\ II}$  and  $f_{SM}$  meaning that none of these forecasts are able to provide more information compared to the forecasts obtained from the Hybrid I model. In contrary, the superiority of the Hybrid I model derived by the forecast evaluation metrics is further extended to show that the dominance of the  $f_{Hybrid\ I}$  is such that it forecast encompasses all the remaining forecasts. The latter result means that the  $f_{Hybrid\ I}$  is providing all that is offered by the rest of the forecasts plus something more.

## 6. CONCLUSION

This paper is exploring the problem of modelling and forecasting volatility of the FTSE MIB index. Firstly, utilizing the Box-Jenkins methodology we construct an ARMA(2,2) model to deal with autocorrelation. Secondly, two asymmetric GARCH models are fitted and compared based on pre-defined criteria. ARMA(2,2)-EGARCH(1,1) with GED distributed errors turned out to be the preferred model. In an attempt to increase the predictive ability of the aforementioned model, two hybrid models are established employing Neural Networks. Hybrid Type I model is a Neural Network having as inputs, apart from the returns and its lagged values, the conditional volatility estimates from the selected EGARCH model. Moreover, the Hybrid Type II model is the preferred EGARCH model enhanced by the inclusion of the output of the Neural Network, which has only the lagged returns as inputs, in its variance equation.

This survey contributes to the literature in the following ways. First, the results uncover that the Hybrid Type I model provides more accurate in-sample and out-of-sample volatility forecasts over the remaining models regardless of the time horizon and the metrics used. Moreover, it is revealed that the superiority of the Hybrid I model is such that it forecast encompasses the rest of the models. Thus, it is recommended to use combinations of GARCH-type models with Neural Networks, with the latter being the base model when dealing with highly volatile markets such as Borsa Italiana. Second, investigating the leverage effect of the Italian stock index, the findings confirm that fluctuations of the stock price in the Italian stock market have asymmetric effects on the volatility of the MIB index, which is in agreement with the literature.

## 7. FUNDING

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

## REFERENCES

- Abounoori, A.A., Naderi, E., Alikhani, N.G., Amiri, A. (2013), Financial Time Series Forecasting by Developing a Hybrid Intelligent System, MPRA Paper 45615. Germany: University Library of Munich.
- Ahmed, A.E.M., Suliman, S.Z. (2011), Modeling stock market volatility using GARCH models evidence from Sudan. *International Journal of Business and Social Science*, 2(23), 114.
- Awartani, B.M., Corradi, V. (2005), Predicting the volatility of the S&P-500 stock index via GARCH models: The role of asymmetries. *International Journal of Forecasting*, 21(1), 167-183.
- Bhattacharya, S., Ahmed, A. (2018), Forecasting crude oil price volatility in India using a hybrid ANN-GARCH model. *International Journal of Business Forecasting and Marketing Intelligence*, 4(4), 446-457.
- Bildirici, M., Ersin, Ö.Ö. (2009), Improving forecasts of GARCH family models with the artificial neural networks: An application to the daily returns in Istanbul stock exchange. *Expert Systems with Applications*, 36(4), 7355-7362.
- Bollerslev, T. (1986), Generalized autoregressive conditional heteroskedasticity. *Journal of Econometrics*, 31(3), 307-327.
- Box, G.E., Jenkins, G.M. (1976), *Time Series Analysis, Control, and Forecasting*. San Francisco, CA: Holden Day. p10.
- Brooks, C. (1998), Predicting stock index volatility: Can market volume help? *Journal of Forecasting*, 17(1), 59-80.
- Brooks, C. (2008), *Introductory Econometrics for Finance*. 2<sup>nd</sup> ed. Cambridge, England: Cambridge University Press.
- Chong, Y.Y., Hendry, D.F. (1986), Econometric evaluation of linear macro-economic models. *The Review of Economic Studies*, 53(4), 671-690.
- Cook, S. (2012), An historical perspective on the forecasting performance of the treasury model: Forecasting the growth in UK consumers' expenditure. *Applied Economics*, 44(5), 555-563.
- Curto, J.D., Pinto, J.C., Tavares, G.N. (2009), Modeling stock markets' volatility using GARCH models with normal, student's t and stable paretian distributions. *Statistical Papers*, 50(2), 311.
- Day, T.E., Lewis, C.M. (1992), Stock market volatility and the information content of stock index options. *Journal of Econometrics*, 52(1-2), 267-287.
- Dickey, D.A., Fuller, W.A. (1979), Distribution of the estimators for autoregressive time series with a unit root. *Journal of the American Statistical Association*, 74(366a), 427-431.
- Dickey, D.A., Fuller, W.A. (1981), Likelihood ratio statistics for autoregressive time series with a unit root. *Econometrica: Journal of the Econometric Society*, 49(4), 1057-1072.
- Donaldson, R.G., Kamstra, M. (1997), An artificial neural network-GARCH model for international stock return volatility. *Journal of Empirical Finance*, 4(1), 17-46.
- Dritsaki, C. (2017), An empirical evaluation in GARCH volatility modeling: Evidence from the Stockholm stock exchange. *Journal of Mathematical Finance*, 7, 366-390.
- Engle, R.F. (1982), Autoregressive conditional heteroscedasticity with estimates of the variance of United Kingdom inflation. *Econometrica: Journal of the Econometric Society*, 50(4), 987-1007.
- Engle, R.F., Patton, A.J. (2007), What good is a volatility model? In: *Forecasting Volatility in the Financial Markets*. Netherlands: Elsevier. p47-63.
- Fahimifard, S.M., Homayounifar, M., Sabouhi, M., Moghaddamnia, A.R. (2009), Comparison of ANFIS, ANN, GARCH and ARIMA techniques to exchange rate forecasting. *Journal of Applied Sciences*, 9(20), 3641-3651.
- Fair, R.C., Shiller, R.J. (1989), The informational content of ex ante forecasts. *The Review of Economics and Statistics*, 71(2), 325-331.
- Franses, P.H., Van Dijk, D. (1996), Forecasting stock market volatility using (non-linear) garch models. *Journal of Forecasting*, 15(3), 229-235.
- Georgescu, V., Dinucă, E.C. (2011), Evidence of improvement in neural-network based predictability of stock market indexes through co-movement entries. In: *Recent Advances in Applied and Biomedical Informatics and Computational Engineering in Systems Applications*. Florence, Italy: 11<sup>th</sup> WSEAS International Conference on Applied Informatics and Communications. p412-417.
- Ghiassi, M.D.K., Zimbra, D.K., Saidane, H. (2006), Medium term system load forecasting with a dynamic artificial neural network model. *Electric Power Systems Research*, 76(5), 302-316.
- Glosten, L.R., Jagannathan, R., Runkle, D.E. (1993), On the relation between the expected value and the volatility of the nominal excess return on stocks. *The Journal of Finance*, 48(5), 1779-1801.
- Güreşen, E., Kayakutlu, G. (2008), Forecasting stock exchange movements using artificial neural network models and hybrid models. In: *International Conference on Intelligent Information Processing*. Boston, MA: Springer. p129-137.
- Güreşen, E., Kayakutlu, G., Daim, T.U. (2011), Using artificial neural

- network models in stock market index prediction. *Expert Systems with Applications*, 38(8), 10389-10397.
- Hajizadeh, E., Seifi, A., Zarandi, M.F., Turksen, I.B. (2012), A hybrid modeling approach for forecasting the volatility of S&P 500 index return. *Expert Systems with Applications*, 39(1), 431-436.
- Heston, S.L. (1993), A closed-form solution for options with stochastic volatility with applications to bond and currency options. *The Review of Financial Studies*, 6(2), 327-343.
- Jarque, C.M., Bera, A.K. (1980), Efficient tests for normality, homoscedasticity and serial independence of regression residuals. *Economics Letters*, 6(3), 255-259.
- Kailas, A. (2012), Prediction of future stock close price using proposed hybrid ANN model of functional link fuzzy logic neural model (FLFNM). *IAES International Journal of Artificial Intelligence*, 1(1), 25.
- Kartsonakis-Mademlis, D., Dritsakis, N. (2018), Volatility between oil prices and stock returns of Dow Jones index: A bivariate GARCH (BEKK) approach. In: *International Conference on Applied Economics (ICOAE)*. Ch. 16. Berlin, Germany: Springer. p209-221.
- Kartsonakis-Mademlis, D., Dritsakis, N. (2020a), Asymmetric volatility spillovers between world oil prices and stock markets of the G7 countries in the presence of structural breaks. *International Journal of Finance and Economics*. Doi: 10.1002/ijfe.1997.
- Kartsonakis-Mademlis, D., Dritsakis, N. (2020b), Does the choice of the multivariate GARCH model on volatility spillovers matter? Evidence from oil prices and stock markets in G7 countries. *International Journal of Energy Economics and Policy*, 10(5), 164-182.
- Khan, A.U., Gour, B. (2013), Stock market trends prediction using neural network based hybrid model. *International Journal of Computer Science Engineering and Information Technology Research*, 3(1), 11-18.
- Ko, P.C. (2009), Option valuation based on the neural regression model. *Expert Systems with Applications*, 36(1), 464-471.
- Koopman, S.J., Jungbacker, B., Hol, E. (2005), Forecasting daily variability of the S&P 100 stock index using historical, realised and implied volatility measurements. *Journal of Empirical Finance*, 12(3), 445-475.
- Kristjanpoller, W., Fadic, A., Minutolo, M.C. (2014), Volatility forecast using hybrid neural network models. *Expert Systems with Applications*, 41(5), 2437-2442.
- Kristjanpoller, W., Minutolo, M.C. (2016), Forecasting volatility of oil price using an artificial neural network-GARCH model. *Expert Systems with Applications*, 65, 233-241.
- Kryzanowski, L., Galler, M., Wright, D.W. (1993), Using artificial neural networks to pick stocks. *Financial Analysts Journal*, 49(4), 21-27.
- Lahmiri, S. (2017), Modeling and predicting historical volatility in exchange rate markets. *Physica A: Statistical Mechanics and its Applications*, 471, 387-395.
- Lewis, N.D. (2017), *Neural Networks for Time Series Forecasting with R: An Intuitive Step by Step Blueprint for Beginners*. United States: CreateSpace Independent Publishing Platform.
- Liu, H.C., Hung, J.C. (2010), Forecasting S&P-100 stock index volatility: The role of volatility asymmetry and distributional assumption in GARCH models. *Expert Systems with Applications*, 37(7), 4928-4934.
- Ljung, G.M., Box, G.E. (1978), On a measure of lack of fit in time series models. *Biometrika*, 65(2), 297-303.
- Lu, X., Que, D., Cao, G. (2016), Volatility forecast based on the hybrid artificial neural network and GARCH-type models. *Procedia Computer Science*, 91, 1044-1049.
- Lu, Y.K., Perron, P. (2010), Modeling and forecasting stock return volatility using a random level shift model. *Journal of Empirical Finance*, 17(1), 138-156.
- Luo, Y., Shah, A. (2007), A local-patch based multi-stage artificial-neural-network training procedure and its application to material characterization. *International Journal of Computational Methods*, 4(3), 439-458.
- Maciél, L.S., Ballini, R. (2010), Neural networks applied to stock market forecasting: An empirical analysis. *Journal of the Brazilian Neural Network Society*, 8(1), 3-22.
- MacKinnon, J.G. (1996), Numerical distribution functions for unit root and cointegration tests. *Journal of Applied Econometrics*, 11(6), 601-618.
- Marcucci, J. (2005), Forecasting stock market volatility with regime-switching GARCH models. *Studies in Nonlinear Dynamics and Econometrics*, 9(4), 6.
- Merh, N., Saxena, V.P., Pardasani, K.R. (2010), A comparison between hybrid approaches of ANN and ARIMA for Indian stock trend forecasting. *Business Intelligence Journal*, 3(2), 23-43.
- Nazarian, R., Alikhani, N.G., Naderi, E., Amiri, A. (2013), Forecasting stock market volatility: A forecast combination approach. *International Research Journal of Finance and Economics*, 111, 56.
- Nelson, D.B. (1991), Conditional heteroskedasticity in asset returns: A new approach. *Econometrica: Journal of the Econometric Society*, 59(2), 347-370.
- Pagan, A.R., Schwert, G.W. (1990), Alternative models for conditional stock volatility. *Journal of Econometrics*, 45(1-2), 267-290.
- Pai, P.F., Lin, C.S. (2005), A hybrid ARIMA and support vector machines model in stock price forecasting. *Omega*, 33(6), 497-505.
- Pakdaman, M., Ahmadian, A., Effati, S., Salahshour, S., Baleanu, D. (2017), Solving differential equations of fractional order using an optimization technique based on training artificial neural network. *Applied Mathematics and Computation*, 293, 81-95.
- Patton, A.J. (2011), Volatility forecast comparison using imperfect volatility proxies. *Journal of Econometrics*, 160(1), 246-256.
- Qi, M. (1999), Nonlinear predictability of stock returns using financial and economic variables. *Journal of Business and Economic Statistics*, 17(4), 419-429.
- Qi, M., Maddala, G.S. (1999), Economic factors and the stock market: A new perspective. *Journal of Forecasting*, 18(3), 151-166.
- Quah, T.S. (2007), Using neural network for DJIA stock selection. *Engineering Letters*, 15(1), 3-8.
- Ramos-Perez, E., Alonso-González, P.J., Núñez-Velázquez, J.J. (2019), Forecasting volatility with a stacked model based on a hybridized artificial neural network. *Expert Systems with Applications*, 129, 1-9.
- Roh, T.H. (2007), Forecasting the volatility of stock price index. *Expert Systems with Applications*, 33(4), 916-922.
- Sahin, S., Tolun, M.R., Hassanpour, R. (2012), Hybrid expert systems: A survey of current approaches and applications. *Expert Systems with Applications*, 39(4), 4609-4617.
- Schittenkopf, C., Dorffner, G., Dockner, E.J. (2000), Forecasting time-dependent conditional densities: A semi non-parametric neural network approach. *Journal of Forecasting*, 19(4), 355-374.
- Soni, S. (2011), Applications of ANNs in stock market prediction: A survey. *International Journal of Computer Science and Engineering Technology*, 2(3), 71-83.
- Sui, X., Hu, Q., Yu, D., Xie, Z., Qi, Z. (2007), A hybrid method for forecasting stock market trend using soft-thresholding de-noise model and SVM. In: *International Workshop on Rough Sets, Fuzzy Sets, Data Mining, and Granular-soft Computing*. Berlin, Heidelberg: Springer. p387-394.
- Tseng, C.H., Cheng, S.T., Wang, Y.H., Peng, J.T. (2008), Artificial neural network model of the hybrid EGARCH volatility of the Taiwan stock index option prices. *Physica A: Statistical Mechanics and its Applications*, 387(1), 1-10.

- Applications, 387(13), 3192-3200.
- Wang, J.J., Wang, J.Z., Zhang, Z.G., Guo, S.P. (2012), Stock index forecasting based on a hybrid model. *Omega*, 40(6), 758-766.
- Wang, Y.H. (2009), Nonlinear neural network forecasting model for stock index option price: Hybrid GJR-GARCH approach. *Expert Systems with Applications*, 36(1), 564-570.
- Wei, L.Y., Chen, T.L., Ho, T.H. (2011), A hybrid model based on adaptive-network-based fuzzy inference system to forecast Taiwan stock market. *Expert Systems with Applications*, 38(11), 13625-13631.
- Wei, W. (2002), Forecasting stock market volatility with non-linear GARCH models: A case for China. *Applied Economics Letters*, 9(3), 163-166.